



Clear Coat Enhancer

Technical Product Information

CLASSIFICATION:

- Protectants

PRODUCT DESCRIPTION:

- Drying agent formulated for use in cold-water rinse arch. When sprayed on a vehicle an immediate water beading/sheeting occurs for faster drying and brilliant vehicle shine.

FEATURES AND BENEFITS:

- Produces immediate water beading/sheeting.
- Used in all drying agent applications.

PHYSICAL CHARACTERISTICS:

- | | |
|------------------------|--------------|
| ▪ Form | Clear Liquid |
| ▪ Color | Light Green |
| ▪ Odor | Light Citrus |
| ▪ Foam | Low |
| ▪ pH (1%) | 4.0 |
| ▪ Specific Gravity | 1.010 |
| ▪ Pounds per Gallon | 8.4 |
| ▪ Phosphorus Content | None |
| ▪ Hard Water Tolerance | Moderate |

APPLICATION GUIDE / USE INSTRUCTIONS:

Recommended Starting Dilutions:

- Use with diaphragm pump into your choice of application. Use approximately 1-2 oz of concentrate per vehicle.

TITRATION PROCEDURE:

- Fill clean vial to 10 ml line of mixed solution
- Add 2 drops of indicator
- Titrate drop by drop with Base 0 and shake vial vigorously between drops.
- End point is reached when clear color is transformed to violet.

CAUTION: Always clean titration vial with cool or cold water. Cleaning vial with warm or hot water could produce irritating vapors. **Gloves and goggles should always be worn when doing titration.**

TITRATION CHART:

- Base 0-starting point: 7-10 Drops

HEALTH, SAFETY, STORAGE & FIRST AID INFORMATION:

See Product MSDS